


cobelPlast

Let's Make Things Last



Physical Properties for A102

The A102 is a high barrier multilayer PP.PA.PP sheet suitable for all range of products which require high barrier for oxygen, gasses, aromas as well as moisture barrier.

The A102 sheet is suitable for aseptic packaging, hot fill, pasteurisation, retort and autoclave processes.

The sheet has excellent machinability on thermoforming equipment designed for PP use. Multiple top and bottom heating is required, forming tool with a PP adapted plug assist and appropriate cooling capacity is a must

General

Composition	PP.PA.PP
Colour	Natural or coloured
Thickness range	250 - 2000 μm
Width	70 - 1500 mm

Physical

Specific weight	0.90 - 0.92 g/cm ³
-----------------	-------------------------------

Thermal

Dimensional stability	<5% (5min @ 190°C)
Thermoforming range	155°C \pm 2°C

Barrier

OTR	1.25 cc/m ² .24h.atm
MVTR	0.2 - 0.3 g/m ² .24h

* typical value for 1mm sheet with 3% PA6/66

Features

- ◆ Suitable for products which required long shelf life
- ◆ Packaging of ready meals, baby food requiring microwave heating, sauces, pet food, jams, juices, ...

Storage conditions and expected product shelf life : it is recommended to store the reels in the original packaging at [5-25]°C - [35-65]%RH and protected from sunlight to guarantee a product life of 12 months

Sheets are manufactured under industrial accepted standards for cGMP. Sheet is composed with components in compliance with EU regulations. Cobelplast is certified ISO 9001:2015, ISO 14001:2015 & BRC/IoP v5



cobelPlast

Let's Make Things Last